

# Why choose Socomec ?



## The vision of a specialist

- Expertise in core technologies.
- Customised solutions.



## The spirit of innovation

- Almost 10% of turnover invested in R&D.



## A culture of independence

- Family shareholding.
- Control of the decision-making process.
- Respect of human values.

# SO easy!

SOCOMECS · 1 rue de Westhouse · 67235 BENFELD Cedex  
Tel. +33 3 88 57 41 41 · info.scp.isd@socomec.com · [www.socomec.com](http://www.socomec.com)

Document non contractuel. © 2017, Socomec SA. Tous droits réservés.  
Ref. DIP-287019 - 03/17 - Photos : Martin Bernhart - Réalisation : SOCOMECS - Pour le respect de l'environnement, ce document a été imprimé sur papier PEFC (Programme for the Endorsement of Forest Certification)

# COMO

Enclosed load break switches  
from 20 to 125 A



## Plug it and use it!

## Wide range

The range offers a wide variety of variants depending on the number of poles, rating and enclosure type.



20 A, 3/4 poles, IEC  
Polycarbonate



25, 32, 40 A, 3/4 poles, IEC  
Polycarbonate



32, 63, 80, 100 A, 3/4/6/8 poles, IEC  
Polycarbonate



63, 125 A, 3/4/6/8 poles, IEC  
Polycarbonate

All-in-one product designed to make your work easier.

## Advantages



### Compact design

Compact enclosures tailored to your needs.



### IP65

The IP65 protection degree provides protection against dust and high pressure water jets for any industrial application.



### Safe

Triple locking of the handle in the OFF position to ensure maximum safety for operators during maintenance operations.

## References

### Size 0

Rating (A)	No. of poles	Reference with (grey/blue handle)	Reference with (yellow/red handle)
20	3	2115 3301	2115 3401

### Size 1

Rating (A)	No. of poles	Reference with (grey/blue handle)	Reference with (yellow/red handle)
25	3	2115 3302	2115 3402
	4	2115 4302	2115 4402
32	3	2115 3303	2115 3403
	4	2115 4303	2115 4403
40	3	2115 3304	2115 3404
	4	2115 4304	2115 4404

### Size 2

Rating (A)	No. of poles	Reference with (grey/blue handle)	Reference with (yellow/red handle)
32	6	2115 6303	2115 6403
	8	2115 8303	2115 8403
63	3	2115 3306	2115 3406
	4	2115 4306	2115 4406
80	3	2115 3308	2115 3408
	4	2115 4308	2115 4408
100	3	2115 3309	2115 3409
	4	2115 4309	2115 4409

### Size 3

Rating (A)	No. of poles	Reference with (grey/blue handle)	Reference with (yellow/red handle)
63	6	2115 6306	2115 6406
	8	2115 8306	2115 8406
125	3	2115 3312	2115 3412
	4	2115 4312	2115 4412